




VX2716 - 27" OMNI 1080P 1MS 100HZ IPS GAMING MONITOR WITH FREESYNC

Key Features


- 27 Inch Full HD (1920x1080p) IPS gaming monitor with thin bezels
- 100Hz refresh rate and 1ms (MPRT) response time for ultimate gaming experience
- AMD FreeSync technology enables fluid and tear-free gameplay
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- The VX2716 supports laptops, PCs, Macs and more with HDMI and DisplayPort inputs







PANEL



1920 x 1080 **RESOLUTION**





GREAT VISUALSFor home entertainment and gaming

Product **Description**

The ViewSonic OMNI™ VX2716 is a 27" gaming monitor that delivers incredible graphics and smooth gameplay at a great price point—perfect for beginners and casual, everyday gamers. Featuring stunning Full HD resolution along with quick refresh rates and response times, the VX2716 is packed with all the features you need for an incredible gaming experience. In addition, dual-integrated speakers deliver immersive stereo sound, while HDMI and DisplayPort offer versatile connectivity, making the monitor a great option for both work and play.

Specifications

Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	80M:1
Light Source	LED
Brightness	300 cd/m2
Colors	16.7M
Aspect Ratio	16:9
Response Time (Typical GTG)	4ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare
Refresh Rate	100Hz
Adaptive Sync	AMD FreeSync™
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio Out	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	28 W
Eco Mode (optimized)	17 W
Consumption (typical)	18 W
Consumption (max)	34 W
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.3 W
Power Supply	Internal
Cable Organization	No
Headphone Hook	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%

VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 115 KHz
Frequency Vertical	48 ~ 100 Hz
Net (lbs)	10.6
Net Without Stand (lbs)	9.0
Gross (lbs)	14.1
Net (kg)	4.6
Net Without Stand (kg)	4.1
Gross (kg)	6.4
Packaging (in.)	26.8 x 17.3 x 5.6
Physical (in.)	24.1 x 17.0 x 9.3
Physical Without Stand (in.)	24.1 x 14.3 x 1.9
Packaging (mm)	680.0 x 440.0 x 143.0
Physical (mm)	612.0 x 432.0 x 237.0
Physical Without Stand (mm)	612.0 x 364.0 x 49.0
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy, CB, RoHS
PACKAGE CONTENTS	VX2716, 3-pin Plug (IEC C13 / CEE22) x1, HDMI Cable (v1.4; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight
LIDC: 766007016002	

UPC: 766907016802

